

## In the United States Patent and Trademark Office

### CERTIFICATE OF EXPRESS MAILING

Number: EL611001697US

Date of Deposit: February 2, 2001

### SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT we, Jason D. Reed, Kai Hu, Robert F. Miracky, and Claude Hilbert, have invented certain new and useful improvements in an

**APPARATUS AND METHOD FOR MICRO-ELECTROMECHANICAL SYSTEMS  
TWO-DIMENSIONAL LARGE MOVEMENT ELECTROSTATIC COMB DRIVE**

**APPARATUS AND METHOD FOR MICRO-ELECTROMECHANICAL SYSTEMS  
TWO-DIMENSIONAL LARGE MOVEMENT ELECTROSTATIC COMB DRIVE**

**Technical Field of the Invention:**

5       The present invention relates to micro-electromechanical systems (MEMS) structures, in particular, to MEMS actuators such as MEMS comb drives.

**Background of the Invention:**

10       Advancement of micro-electromechanical systems (MEMS) technology and general trends toward miniaturization of devices, structures, or subsystems could significantly benefit a variety of control or communication systems. Typically, MEMS structures employed in such control or communication systems include a MEMS actuator such as a MEMS comb drive to provide displacement functionality in diverse applications including, opto-electronic communication systems, and high-speed sensor systems. When MEMS actuators are integrated with optical devices, for example, micro-optical elements such as lenses, they may provide an efficient means for manipulating a received optical beam or signal. However, integration of such a MEMS actuator with a micro-optical element or sensor system may not meet the requirements for desired displacement functionality. In addition, by simply using suitable semiconductor, substrate, and/or conductive material layers to form a multilevel layered miniature structure, it can be difficult to provide robust and reliable MEMS actuators capable of large movements.

20       Often, deployment of MEMS actuators such as a MEMS comb drive, in an optical communication or sensor system, could allow fabrication of inexpensive and batch-fabricated integrated MEMS optical or MEMS sensor devices, respectively. Despite seemingly obvious advantages of such MEMS actuators for optical or sensor applications, systems and methods for forming these MEMS actuators that are required to meet increasingly demanding displacement functionality are desired.

25       A variety of MEMS actuators generally include a stage and one or more support members such as folded suspension members or spring bars, which are devised to suspend the stage. In a

MEMS comb drive actuator, a typical stage may include one or more comb drive structures, each comb drive structure having interdigitated fingers to enable its operation responsive to an applied actuation.

In operation, actuation to a MEMS actuator such as a MEMS comb drive is oftentimes provided by an actuation force such as an electrostatic force being applied to either a selected comb drive structure or a particular set of comb drive structures for causing a desired displacement of the stage in a selected direction. For example, a suitable voltage bias may be applied to a first set of comb drive structures to result in the x-axis displacement of the stage in the horizontal direction.

Regardless of the type of a MEMS actuator employed, oftentimes a set of structural, electrical, and operational characteristics govern the functionality of a MEMS actuator based system and their potential applications. In general, structural and electrical characteristics such as response rates, design compactness, and/or power consumption can be utilized to characterize most MEMS actuators. For example, high response rates such as 100 $\mu$ s or less, dimensions on the order of 1 mm or less, and/or power consumption typically less than 1 mW at maximum speed could be desirable for a particular application.

Operational characteristics such as suspension member deformation and a particular actuation scheme can also specify a MEMS actuator application domain. However, it could be difficult to build MEMS actuators including MEMS comb drive actuators that may provide relatively large displacements, for example, greater than 10  $\mu$ m. Providing simultaneous displacements in multiple axes, for example, in two axes such as x-axis in horizontal direction and y-axis in vertical direction could be even more difficult. In addition, significantly high drive voltages in a particular range may be required for a controlled and precise operation of a MEMS actuator.

In general, it is difficult to completely avoid some deformation of support members due to suspension and actuation. For example, typically, an undesirable degree of deformation including bending, compression or extension occurs responsive to an applied actuation in support members such as spring bars or alike. To avoid any appreciable affect of these undesirable

deformations of support members in a MEMS actuator based integrated device; it is desirable to devise the MEMS actuator with appropriate structural, electrical, and operational characteristics.

FIG. 1A is a top plan view of a prior art MEMS unidirectional comb drive 100. MEMS unidirectional comb drive 100 is useful in explaining an exemplary embodiment of the invention, as described later in the context of a bi-directional comb drive. MEMS unidirectional comb drive 100 may comprise a shuttle 105, the movable portion, and a stator 110, the anchor portion. Shuttle 105 may include a spring 115 comprising a horizontal bar 120 and a vertical bar 125. Shuttle 105 and stator 110 may be anchored at anchors 130A and 130B, respectively. MEMS unidirectional comb drive 100 may include a set of interdigitated fingers for selectively positioning shuttle 105 responsive to an appropriate actuation force. The actuation force may cause a controlled displacement of shuttle 105 relative to stator 110. Such displacement enables a selective orientation of MEMS unidirectional comb drive 100 at a desired position, which may be generally determined by the amount of displacement, in response to the actuation. Spring 115 could be devised of a desired geometry to generally provide a particular range of displacement responsive to a specific type of actuation force such as an electrostatic force. For example, a voltage bias may be applied between shuttle 105 and stator 110.

In the illustrated exemplary embodiment of FIG. 1A, shuttle 105 having a shuttle anchor side 132 comprises a first set of fingers 135A through 135D. Likewise, stator 110 having a stator anchor side 137 comprises a second set of fingers 140A through 140C. Both the first and second set of fingers 135A through 135D and 140A through 140C are advantageously configured in an interlocked manner. Spring 115 may be coupled between shuttle anchor side 132 and anchor 130A. More specifically, horizontal bar 120 may be fixedly coupled to shuttle anchor side 132 and vertical bar 125 may be fixedly connected to anchor 130A. For stator 110, stator anchor side 137 may be adapted to fixedly connect to anchor 130B.

In operation, MEMS unidirectional comb drive 100 may be selectively displaced responsive to an actuation being applied in the form of an electrostatic force. With continuing reference to FIG. 1A, MEMS unidirectional comb drive 100 could be actuated to move in a x-direction as indicated by a horizontal arrow 142. More specifically, when a voltage bias is

applied between the moving part (shuttle 105) and the anchor part (stator 110), the electrostatic force generated from the applied voltage bias will drive the comb drive 100 to move in the x-direction. The amount of displacement is generally determined by balancing the electrostatic force and spring reaction force according to the relationship as shown below in equation 1.

$$(1) \quad F = -\frac{\partial U}{\partial x} = \frac{N\epsilon V^2}{2d} = kx$$

Where: V is the applied voltage bias, x the shuttle displacement, N the number of fingers, k the stiffness of the spring(s),  $\epsilon$  the air permittivity, and d the gap of fingers (as shown in FIG. 1A).

Two significant aspects are to be noted here. First, the comb drive displacement is independent of the interlocked length (shown in the FIG. 1A as "1-x") between two combs. This is due to the fact that the electrostatic potential is linearly proportional to the interlocked length, and the force is the derived gradient of the potential, which becomes constant. Second, the displacement is inversely proportional to the stiffness "k" of the springs. In the present case, the spring is made of a long vertical and short horizontal bar. When the comb moves in x-direction, both bars will contribute to the displacement. The percentage of their contribution will, however, be quite different. It is observed that the vertical bar undergoes bending and the horizontal bar the extension. To understand the relative significance of bending and extension, we consider two bars of the same length with a spring bar cross-section of 4x4 micron, driven by 100 V bias on a comb drive of 20 fingers with the finger gap of 4 micron.

Unfortunately, in a two-dimensional comb drive it is even more difficult to avoid deformation and movement of a first set of comb drives while actuating and displacing a second set of comb drives connected to the first set of comb drives. For instance, while performing excursions using the first set of comb drives, in one direction such as the x-axis, it is highly desirable to prevent any displacement along that same axis of the second set of comb drives which may control the motion in the y-axis. Such robust MEMS actuators could operate as a building block in a variety of opto-electromechanical equipment.

Accordingly, there is a need for two-dimensional micro-electromechanical systems (MEMS) comb drive actuator, which may be controllably oriented at a desired position.

**Summary of the Invention:**

10 The present invention generally provides micro-electromechanical systems (MEMS) structures, in particular, MEMS actuators such as comb drives. In an exemplary embodiment, a comb drive apparatus includes a first set of comb pairs and a second set of comb pairs coupled to the first set of comb pairs. A stage may be coupled to the first and second sets of comb pairs. A first plurality of springs may be interposed between the second set of comb pairs and the stage and between the second set of comb pairs and the first set of comb pairs for movably coupling the second set of comb pairs to the stage and to the first set of comb pairs. Likewise, a second plurality of springs may be interposed between the first set of comb pairs and the stage and between the first set of comb pairs and the second set of comb pairs for movably coupling the first set of comb pairs to the stage and to the second set of comb pairs.

15 The stage may be suspended, electrically conductive, and mechanically operable to permit a controlled displacement thereof in first and second directions responsive to respective first and second actuating forces such as electrostatic forces of appropriate bias. The first actuation force to the first set of comb pairs may provide a first displacement to the stage in the first direction, and the second actuation force to the second set of comb pairs may provide a second displacement to the stage in the second direction. The first actuation force may cause a bending of the first plurality of springs while the second plurality of springs being maintained substantially straight to provide the first displacement. The second actuation force may cause a bending of the second plurality of springs while the first plurality of springs being maintained substantially straight to provide the second displacement.

20 Each spring of the first plurality of springs may be disposed in a first orientation and each spring of the second plurality of springs may be disposed in a second orientation being substantially orthogonal to the first orientation. In addition, each spring of the first and second pluralities of springs could be formed as a bar.

25 In an another embodiment, a comb drive apparatus includes a first set of comb pairs, a second set of comb pairs coupled to the first set of comb pairs, and a suspended stage coupled to the first and second sets of comb pairs. Each comb pair of the first set of comb pairs having a

first fixed comb and a first movable comb. The first movable comb may include first and second ends being connected by a first support. Each comb pair of the second set of comb pairs having a second fixed comb and a second movable comb. The second movable comb may include first and second ends being connected by a second support.

5 Each first spring of the first and second pluralities of first springs having a first end and a second end. The first ends of the first plurality of first springs being connected to the suspended stage and the second ends of the first plurality of first springs being connected to the respective second support of the second movable combs. And the first ends of the second plurality of first springs being connected to the respective first movable comb and the second ends of the second plurality of first springs being connected to the respective first end or second end of the second movable combs, thereby movably coupling the second set of comb pairs to the suspended stage and to the first set of comb pairs.

10 Each second spring of the first and second pluralities of second springs having a first end and a second end. The first ends of the first plurality of second springs being connected to the suspended stage and the second ends of the first plurality of second springs being connected to the respective first support of the first movable combs. And the first ends of the second plurality of second springs being connected to the respective second movable comb and the second ends of the second plurality of second springs being connected to the respective first end or second end of the first movable combs, thereby movably coupling the first set of comb pairs to the suspended stage and to the second set of comb pairs.

20 In operation, said first set of comb pairs may provide a first displacement to the suspended stage in a first direction in response to a first electrostatic force. The second set of comb pairs may provide a second displacement to the suspended stage in a second direction in response to a second electrostatic force. The first electrostatic force may cause a controlled bending of the first and second pluralities of first springs for displacing the first movable combs while the first and second pluralities of second springs being maintained substantially straight for preventing displacement of the second movable combs. The second electrostatic force may cause a controlled bending of the first and second pluralities of second springs for displacing the

second movable combs while the first and second pluralities of first springs being maintained substantially straight for preventing displacement of the first movable combs.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000  
1005  
1010  
1015  
1020  
1025  
1030  
1035  
1040  
1045  
1050  
1055  
1060  
1065  
1070  
1075  
1080  
1085  
1090  
1095  
1100  
1105  
1110  
1115  
1120  
1125  
1130  
1135  
1140  
1145  
1150  
1155  
1160  
1165  
1170  
1175  
1180  
1185  
1190  
1195  
1200  
1205  
1210  
1215  
1220  
1225  
1230  
1235  
1240  
1245  
1250  
1255  
1260  
1265  
1270  
1275  
1280  
1285  
1290  
1295  
1300  
1305  
1310  
1315  
1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220  
10225  
10230  
10235  
10240  
10245  
10250  
10255  
10260  
10265  
10270  
10275  
10280  
10285  
10290  
10295  
10300  
10305  
10310  
10315  
10320  
10325  
10330  
10335



10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100

In an another alternate exemplary embodiment, a two-dimensional comb drive apparatus including a set of horizontal comb pairs, each of the horizontal comb pair having a horizontal fixed comb and a horizontal movable comb, the horizontal movable comb including first and second ends being connected by a horizontal support; a set of vertical comb pairs coupled to the set of horizontal comb pairs, each of the vertical comb pair having a vertical fixed comb and a vertical movable comb, the vertical movable comb including first and second ends being connected by a vertical support; a suspended stage coupled to the sets of horizontal and vertical comb pairs; first and second pluralities of horizontal springs, each horizontal spring having a first end and a second end, the first ends of the first plurality of horizontal springs being connected to the suspended stage and the second ends of the first plurality of horizontal springs being connected to the respective vertical support of the vertical movable combs, and the first ends of the second plurality of horizontal springs being connected to the respective horizontal movable comb and the second ends of the second plurality of horizontal springs being connected to the respective first end or second end of the vertical movable combs, thereby movably coupling the set of vertical comb pairs to the suspended stage and to the set of horizontal comb pairs; and first and second pluralities of vertical springs, each vertical spring having a first end and a second end, the first ends of the first plurality of vertical springs being connected to the suspended stage and the second ends of the first plurality of vertical springs being connected to the respective horizontal support of the horizontal movable combs, and the first ends of the second plurality of vertical springs being connected to the respective vertical movable comb and the second ends of the second plurality of vertical springs being connected to the respective first end or second end of the horizontal movable combs, thereby movably coupling the set of horizontal comb pairs to the suspended stage and to the set of vertical comb pairs.

In an another alternate exemplary embodiment, a method for forming a two-dimensional comb drive, comprising: providing a first set of comb pairs; providing a second set of comb pairs coupled to the first set of comb pairs; providing a stage coupled to the sets of first and second comb pairs; providing a first plurality of springs interposed between the second set of comb pairs and the stage and between the second set of comb pairs and the first set of comb pairs for

movably coupling the second set of comb pairs to the stage and to the first set of comb pairs; and providing a second plurality of springs interposed between the first set of comb pairs and the stage and between the first set of comb pairs and the second set of comb pairs for movably coupling the first set of comb pairs to the stage and to the second set of comb pairs.

- 5       The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter which form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims.

10776466.02001

**Brief Description of the Drawings:**

For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

5        FIG. 1A is a top plan view of a prior art micro-electromechanical systems (MEMS) unidirectional comb drive.

FIG. 1B is a graph of exemplary displacements due to bending and extension for a MEMS comb drive.

FIG. 2A is a top plan view of an exemplary embodiment of a MEMS fully suspended bi-directional comb drive consistent with one aspect the present invention.

FIG. 2B is a top plan view of the MEMS fully suspended bi-directional comb drive of FIG. 2A actuated in x-axis (horizontal direction) in accordance with one aspect of the present invention.

FIG. 3 is a graph of an exemplary variation of displacements for the MEMS fully suspended bi-directional comb drive of FIG. 4A with different spring lengths.

FIG. 4A is a top plan view of an exemplary MEMS inter-linked bi-directional comb drive.

FIG. 4B is a top plan view of an exemplary MEMS nested bi-directional comb drive.

20        FIG. 5 is a top plan view of an exemplary embodiment of a MEMS fully suspended bi-directional comb drive actuator for optical applications consistent with one aspect the present invention.

FIG. 6A is a top plan view of the MEMS fully suspended bi-directional comb drive actuator of FIG. 5 actuated in x-axis (horizontal direction).

25        FIG. 6B is a top plan view of the MEMS fully suspended bi-directional comb drive actuator of FIG. 5 actuated concurrently in x-axis (horizontal direction) and y-axis (vertical direction).

5

FIG. 7B is a top plan view of the MEMS fully suspended bi-directional comb drive actuator of FIG. 7A actuated in y-axis (vertical direction).

### Detailed Description

A Micro-electromechanical systems (MEMS) actuator such as a MEMS comb drive generally comprises comb pairs, each comb pair may include a fixed comb and a movable comb coupled to a plurality of suspension members, such as springs bars, or the like. Suspension members are generally utilized to support the movable combs. Suspension members may be suitably devised to enable a controlled operation of the MEMS comb drive. An actuation force such as an electrostatic force may be selectively applied to the comb pairs for orienting the MEMS comb drive at a desired position. The present invention is generally directed to such MEMS comb drives, which could be utilized for realizing a variety of control and/or communication systems.

One exemplary embodiment of the present invention is generally described with respect to a MEMS fully suspended bi-directional comb drive, which includes suspension members as spring bars. The geometric features for the spring bars can be readily devised using a conventional photolithography based micro-fabrication process. In an exemplary embodiment, a suitable micro-fabrication technology, in a known manner, is generally employed to fabricate the chip-scale or miniature device of the present invention useful for a variety of optical applications. For example, an optical MEMS actuator may be advantageously devised to integrate with one or more micro-optical elements such as micro-lenses or micro-mirrors. The present invention should, however, not necessarily be restricted to the field of micro-optical elements and/or comb drive actuators, as will be readily evident. Like reference numerals refer to similar elements throughout the drawings.

FIG. 1B is a graph of exemplary displacements (in meters) due to bending and extension for a MEMS comb drive such as the MEMS unidirectional comb drive 100 of FIG. 1A. It is observed that the displacement due to bending is an order or two magnitudes larger than the displacement due to the extension. In fact, the displacement due to the extension can be practically neglected. This observation bears significant implications for bi-directional or two-dimensional comb drives.

FIG. 2A is a top plan view of an exemplary embodiment of a MEMS fully suspended bi-directional comb drive 200 consistent with one aspect the present invention. A relatively simple but representative design of MEMS fully suspended bi-directional comb drive 200 may comprise vertical spring bars 205A through 205L and horizontal spring bars 210A through 210H to fully suspend a movable portion without touching a fixed portion. The MEMS fully suspended bi-directional comb drive 200 may further comprise a first set of horizontal combs 212A, 212B and a second set of vertical combs 213A, 213B. Each of the first set of horizontal combs 212A, 212B includes a pair of oppositely disposed combs with one comb being movable and the other being fixed. In particular, the horizontal comb 212A includes a fixed comb 214A and a movable comb 215A.

The fixed portion may include fixed combs 214A through 214D. Likewise, the movable portion may include movable combs 215A through 215D and an inter-linked stage 220. Each movable comb 215 is generally attached by both associated horizontal and vertical spring bars. For example, movable comb 215A is attached to horizontal spring bars 210A, 210B and vertical spring bars 205B through 205E. This pattern of spring distribution is advantageously employed to exploit the bending versus extension behavior as illustrated in FIG. 1B to achieve relatively large bi-directional movement without being limited by finger spacing.

FIG. 2B is a top plan view of the MEMS fully suspended bi-directional comb drive 200 of FIG. 2A actuated in x-axis (horizontal direction 225). Thus, when the left and right combs are actuated in x-direction, the horizontal displacement will make all vertical spring bars 205A through 205L bend by approximately the same amount, but the horizontal spring bars 210A through 210H assume very little deformation since bending is the dominating deformation as opposed to extension. Therefore, the movement in top and bottom combs 215A and 215C, respectively, can be negligible (as indicated from the deformed shape in FIG. 4B). Accordingly, the movement in horizontal direction 225 is not going to cause vertical comb fingers to touch each other. Similarly, actuation in the vertical direction is not going to cause horizontal comb finger interference. Thus, MEMS fully suspended bi-directional comb drive 200 can achieve large x and y displacements without being limited by comb finger spacing. Moreover, MEMS

05776166-1000201

fully suspended bi-directional comb drive 200 has a decent form factor, enough real estate for center mass distribution, and equal participating mass in x- and y-direction actuation. It shores the advantages of both inter-linked and nested comb drives.

As persons skilled in the art will appreciate that using a typical micro-fabrication process, in a known manner, the MEMS fully suspended bi-directional comb drive 200 may be readily fabricated. For example, employing a substrate layer and a conductive layer, the MEMS fully suspended bi-directional comb drive 200 may be formed through a deposition and patterning process. In particular, the first set of horizontal combs 212A, 212B, second set of vertical combs 213A, 213B, inter-linked stage 220, and vertical spring bars 205A through 205L and horizontal spring bars 210A through 210H may be formed from a single layer. For example, a layer of polysilicon may be utilized to form the MEMS fully suspended bi-directional comb drive 200. Additionally, the vertical spring bars 205A through 205L and horizontal spring bars 210A through 210H could be suitably attached to the substrate layer to form anchors. For example, vias may be devised for anchoring the MEMS fully suspended bi-directional comb drive 200.

However, it is to be understood that the movable combs 215A through 215D of the MEMS fully suspended bi-directional comb drive 200 may or may not share the same anchors at the four corners of the structure as depicted in FIGS. 2A and 2B. For example, the vertical spring bar 205A and the horizontal spring bar 210A could be anchored separately.

In an exemplary embodiment, one-micron thick layer of polysilicon may be used as the primary composition of the single conductive layer. However, other materials or combinations of materials may be employed, which can be deposited and patterned according to a desired specification over a particular substrate layer.

In operation, a two-dimensional comb drive such as the MEMS fully suspended bi-directional comb drive 200 may be controllably oriented at a desired position responsive to an appropriate actuation. Specifically, undesired deformation and movement of the second set of vertical combs 213A, 213B while actuating and displacing the first set of horizontal combs 212A, 212B coupled to the second set of vertical combs 213A, 213B can be significantly reduced by appropriate shapes, positions, and combinations thereof for the vertical spring bars 205A

through 205L and horizontal spring bars 210A through 210H. Likewise, undesired deformation and movement of the first set of horizontal combs 212A, 212B while actuating and displacing the second set of vertical combs 213A, 213B coupled to the first set of horizontal combs 212A, 212B can also be significantly reduced. For instance, while performing excursions using the second set of vertical combs 213A, 213B, in one direction such as the x-axis, selective bending of the vertical spring bars 205A through 205L and stiffness of the horizontal spring bars 210A through 210H may prevent substantial displacement along that same axis of the movable combs 215A through 215D of the first set of horizontal combs 212A, 212B which may control the motion in the y-axis.

FIG. 3 is a graph of a range of exemplary displacements calculated for the MEMS fully suspended bi-directional comb drive 200 of FIG. 2A for different spring bar lengths. It is to be understood that as shown in FIG. 2A just straight bars may function as springs. Moreover, the MEMS fully suspended bi-directional comb drive 200 can be readily devised to provide maximum displacements in x or y directions through parametric optimization of spring pattern and spring distribution.

In an exemplary embodiment, MEMS fully suspended bi-directional comb drive 200 comprises a conductor or semi-conductor, with each pair of opposing combs having 20 to 19 interdigitated fingers. The spring bar cross-section is 3x4 microns, i.e. 3 microns thickness and 4 microns width, and the fingers are 8 microns long with a gap between fingers of 2 microns. As an example, the length of vertical spring bars 205A through 205L is devised twice the length of horizontal spring bars 210A through 210H. As shown in FIG. 3, displacements greater than 10 microns are attainable for spring bar lengths greater than 500 microns. Persons skilled in the art will recognize that such geometric features are readily achievable using generally known photolithography based micro-fabrication manufacturing processes. The foregoing describes only one embodiment of the invention and many variations of the embodiment will be obvious for a person skilled in the art of semiconductor, micro-electromechanical fabrication. Certainly, various other materials and techniques can be utilized in the construction of the various layers.



FIG. 4A is a top plan view of an exemplary MEMS inter-linked bi-directional comb drive 425. In this configuration, four exterior combs 430A through 430D (two horizontal and two vertical) are anchored, and four internal combs 435A through 435D are inter-linked via an inter-link 440. A desired movement or displacement of the inter-linked combs in x-direction as indicated by an arrow 445, can be achieved by applying an appropriate voltage between the two exterior horizontal combs 430A and 430C and the inter-linked internal combs 435A through 435D. Likewise, in y-direction as indicated by an arrow 447, a movement can be achieved by applying a suitable voltage between the two exterior vertical combs 430B and 430D and the inter-linked internal combs 435A through 435D. Among many advantages, the main advantages of the inter-linked comb drives are decent form factor (x-y dimensions can be the same), and achievable equal or similar electrostatic driving force. However, both x- and y-directional movements can be limited by a finger gap 449 (assuming all exterior and internal combs are identical in shape and size). For example, when the amount of displacement in the x-direction 445 exceeds the finger gap 449, the vertical fingers of the anchored combs 430B and 430D and movable combs 435B and 435D will touch each other, creating an electrical short. This factor could become even more exacerbated in applications where the finger gap 449 has to be small to obtain enough driving force.

FIG. 4B is a top plan view of an exemplary MEMS nested bi-directional comb drive 465. MEMS nested bi-directional comb drive 465 may include horizontal or external combs 470A, 470B and vertical or nested combs 470C and 470D. With reference to FIGS. 4A and 4B, a desired movement in the x-direction 445 can be achieved by appropriately driving horizontal combs 470A, 470B. Likewise, a movement in y-direction 447 may be achieved by suitably driving the vertical combs 470C and 470D, which are rigidly nested within the movable-part frame of horizontal combs 470A, 470B. When an external comb drive is in action and a movement in the x-direction 445 is actuated, the movable and fixed parts of the nested combs 470C and 470D moves the same amount. On the other hand, when the nested combs 470C and 470D are in action and a vertical displacement in the y-direction 447 is actuated, the external

combs 470A and 470B are fully anchored. Therefore, this design may completely eliminate the x-y motion interference. Accordingly, the displacement may not be limited by finger gap.

However, nested spring and combs generally occupy the internal spaces and reduce the real estate and flexibility for mass distribution. In addition, to achieve the same actuation force, the nested combs 470C and 470D may have to assume a geometry (e.g. comb spacing, finger size) different from the external combs 470A and 470B, thereby increasing process complexity. Moreover, the actuation mass in the x-direction 445 is different from that in the y-direction 447, as the movement in the x-direction 445 carries the complete nested combs 470C and 470D, but the movement in y-direction 447 only moves the external combs 470A and 470B.

FIG. 5 is a top plan view of an exemplary embodiment of a MEMS fully suspended bi-directional actuator 500 consistent with one aspect of the present invention. The MEMS fully suspended bi-directional actuator 500 may comprise a micro-frame 503 to receive a micro-optical element such as a micro-lens or a micro-mirror and comb drives 505A through 505D. Each comb drive includes a fixed comb configured in interdigitated fashion with an associated movable drive. For example, comb drives 505A through 505D each comprise a fixed comb 510, 510A through 510D, and an associated movable comb 515, 515A through 515D, respectively. In shown embodiment of FIG. 5, the comb drives 505A through 505D are identical. However, different sizes, shapes or forms of comb drives 505A through 505D could be devised. Moreover, micro-frame 503 may be devised to connect with movable combs 515A through 515B via spring bars 520A through 520D.

Each movable comb, 515A through 515D may include first and second ends extended longitudinally for fixedly connecting the movable comb to a substrate 525, thereby suspending the MEMS fully suspended bi-directional actuator 500. To couple fixed combs 510A through 510D to the substrate 525, anchors 530A through 530D, respectively, may be utilized. However, it should be appreciated that fixed combs 510A through 510D may be coupled differently to the substrate 525. Each comb drive 505 may include a set of interdigitized fingers. More specifically, each fixed and movable combs 510, 515 may comprise a plurality of fingers to form the set of interdigitized fingers. For example, fixed comb 510A may include a first set of fingers

535A and movable comb 515A may include a second set of fingers 540A. As shown in FIG. 5, the first set of fingers 535A could include nineteen fingers with each finger having 10 microns of width and generally interposed at 8 microns in separation from the adjacent finger. Moreover, fingers may comprise a metal layer.

5 It is to be understood that the MEMS fully suspended bi-directional actuator 500 may be fabricated with MEMS technology generally utilizing a known surface micro-machining manufacturing process. The depicted actuator 500 could be advantageously utilized for a variety of optical applications. For example, micro-optics can be readily integrated with the actuator 500 to enable optical communications. In one embodiment, a micro-lens may be disposed in the micro-frame 503 for manipulating any optical signals projected therethrough.

10 In operation, MEMS fully suspended bi-directional actuator 500 may selectively micro-position the micro-lens in response to an actuating force such as an electrostatic force being applied through an actuation voltage. When an appropriate actuation voltage is placed across either the first and second set of fingers 535A, 540A, an electrostatic charge may be generated therebetween. In turn, movable comb 515A may be displaced. For example, when the comb drive 505A may be actuated, first movable comb 515A may be pulled towards the associated fixed comb 510A. In one embodiment, actuation voltage of 50 Volts is used for providing a maximum displacement of 5 microns.

15 FIG. 6A is a top plan view of the MEMS fully suspended bi-directional comb drive actuator 500 of FIG. 5 actuated in x-axis (horizontal direction). A pre-actuated position of the actuator 500 is indicated by a dotted structure 605. Upon proper actuation, a portion of the MEMS fully suspended bi-directional comb drive actuator 500 is displaced. A post-actuated position of the actuator 500 is illustrated by a stretched structure 610.

20 FIG. 6B is a top plan view of the MEMS fully suspended bi-directional comb drive actuator 500 of FIG. 5 actuated concurrently in x-axis (horizontal direction) and y-axis (vertical direction). A pre-actuated position of the actuator 500 is depicted by a dotted structure 650. When appropriately actuated, a portion of the MEMS fully suspended bi-directional comb drive actuator 500 is displaced. Accordingly, a post-actuated position of the actuator 500 is illustrated

by a moved structure 655. With reference to FIGS. 6A and 6B, displacements of more than 10 microns may be readily attainable. It should be appreciated that significantly larger displacements could be achieved with finer geometric features, even at a reduced spring length.

FIG. 7A is a top plan view of another exemplary embodiment of a MEMS fully  
5 suspended bi-directional comb drive actuator 700 for optical applications in accordance with one aspect the present invention. MEMS fully suspended bi-directional comb drive actuator 700 may include an array of micro-frames 705. FIG. 7B is a top plan view of the MEMS fully suspended bi-directional comb drive actuator 700 of FIG. 7A actuated in y-axis (vertical direction). A pre-actuated position of the actuator 700 is indicated by a dotted structure 750. Upon proper  
10 actuation, a portion of the MEMS fully suspended bi-directional comb drive actuator 700 is displaced. A post-actuated position of the actuator 700 is illustrated by a stretched structure 755.

Accordingly, an apparatus and method for a micro-electromechanical systems (MEMS) actuator such as a MEMS two-dimensional electrostatic comb drive having springs being  
15 advantageously configured to provide relatively large movements in first and second directions is generally disclosed. In response to an appropriate electrostatic actuation force being applied to the MEMS two-dimensional electrostatic comb drive, the springs enable controlled displacement along both x-axis (horizontal direction) and y-axis (vertical direction).

Although the present invention and its advantages have been described in detail, it should  
20 be understood that various changes, substitutions and alterations can be made to the embodiments herein without departing from the spirit and scope of the invention as defined by the appended claims. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will  
25 readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present

*Attorney Docket No.: TERY:002US*

invention. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

We claim:

09776166 020201